

HIGHLIGHTS

- LOW POWER, FANLESS
- LCD 8,0" 800x600 WITH TOUCH-SCREEN
- 3,5" SINGLE BOARD COMPUTER
- CPU AMD LX 800, 500MHZ, 512MB RAM
- COMPACT FLASH 2GBYTE INDUSTRIAL GRADE
- METAL HOUSING, POWDER COATED
- CE-COMPLIANT, FOR INDUSTRIAL APPLICATIONS
- AVAILABILITY MIN. 3 YEARS



SAC 08-LX800

Update: 01/2016

Hardware	Description
Type of device	Industrial all-in-one PC with steel sheet housing; integrated 3,5" single board computer, 8,0" display 800x600p; resistive touch screen, VESA attachment.
CPU	Type: AMD Geode LX 800, 500MHz 512MB RAM (SO-DDR)
Interfaces external	Serial: 1x COM(RS232), 2x USB Graphics: CRT (VGA) Network: 2x LAN10/100/1000 Mbps Fast Ethernet Keybd. entry: PS/2 (keyboard)
Touch screen	Type: Resistive touch screen 4-wire, USB controller
Main memory	RAM 1x 512MB DDR RAM SO-DIMM (max. 1GB)
Mass memory	CF: CompactFlash™ Type I – max. 16GB industrial grade optional 2,5" HDD
Display	LCD: 8,0" 300cd/m² 800x600 pixel
Power supply AC	Form factor: max. 3" x 5" (76,2x127mm) open frame Input: 90-264 VAC / 47- 440Hz Output: +5VDC / +12VDC / -12VDC Wattage: max. 60W
Power supply DC	Input: 9-36 VDC Output: +5VDC-10A / +12VDC

Software	Description
Operation system	Windows® 7 / 8.1 / 10 and embedded versions, others on request

Mechanics	Dimensions: W x H x D
Housing	240 x 176 x 70 mm
Weight	3,0 kg

Options	Description
Mounting	VESA attachment 60x60, pivot arm for turning, lateral buckling & locking device, foot.

© 2016 MASS GmbH